



JCB POWER PRODUCTS | QS GENERATOR RANGE

Power 50Hz: 20 - 220kVA / 60Hz: 18 - 165kW



LIVELINK FOR POWER.

JCB LIVELINK PUTS THE POWER IN YOUR HANDS. REVOLUTIONISE THE WAY YOU MONITOR AND MANAGE YOUR POWER GENERATORS TO MAXIMISE PRODUCTIVITY, DECREASE RUNNING COSTS AND INCREASE EFFICIENCY.

Data and insight – Keep the productivity high to keep the power on with JCB LiveLink. Real-time information keeps you in complete control to let you monitor and manage your power generators remotely via a PC or Smartphone.



Monitor and manage – The most up-to-date information about how your generators are performing or where they are located becomes even more critical when it comes to making the right decisions. The more knowledge you have to generate uptime, the better value for money your generator delivers.

Optimised Fleet Management – Whether you have one generator or an entire fleet, LiveLink can provide a powerful reporting tool to deliver higher machine availability, improved fleet control and enhanced machine value, accessed via an online portal.

VALUE ADDED.

JCB'S WORLDWIDE CUSTOMER SUPPORT IS FIRST CLASS. WHATEVER YOU NEED AND WHEREVER YOU ARE, WE'LL BE AVAILABLE QUICKLY AND EFFICIENTLY TO HELP MAKE SURE YOUR MACHINERY IS PERFORMING TO ITS FULL POTENTIAL.




Our Technical Support Service provides instant access to factory expertise, day or night, while our Finance and Insurance teams are always on hand to provide fast, flexible, competitive quotes.

JCB Assetcare offers comprehensive extended warranties and service agreements, as well as service-only or repair and maintenance contracts. Irrespective of what you opt for, our maintenance teams around the world charge competitive labour rates, and offer non-obligation quotations as well as fast, efficient insurance repair work.

The global network of JCB Parts Centres is another model of efficiency; with 16 regional bases, we can deliver around 95% of all parts anywhere in the world within 24 hours. Our genuine JCB parts are designed to work in perfect harmony with your machine for optimum performance and productivity.




* JCB Assetcare may not be available in your region, so please check with your local dealer.

Model	Type - Open, Canopy, Container	Engine	PRIME POWER (PRP)		STANDBY POWER (ESP)		DIMENSIONS (mm)			
			50Hz 400V (kVA)	50Hz 400V (kVA)	60Hz 480V (kW)	60Hz 480V (kW)	Length (mm)	Width (mm)	Height (mm)	Weight Including Oil and Water
G65QS/ G66QS*		JCB 4-Cylinder	59	65	59	65	2750	1140	1830	1660
G65S		JCB 4-Cylinder	59	65	59	65	2300	1030	1750	1360
G90QS/ G91QS*		JCB 4-Cylinder	80	88	70	77	2850	1140	1830	1780
G90S		JCB 4-Cylinder	80	88	70	77	2300	1030	1750	1450
G115QS/ G116QS*		JCB 4-Cylinder	105	116	86	95	2850	1140	1830	1830
G115S		JCB 4-Cylinder	105	116	86	95	2300	1030	1750	1500
G140QS/ G141QS*		JCB 4-Cylinder	125	138	101	111	2850	1140	1830	1880
G140S		JCB 4-Cylinder	125	138	101	111	2300	1030	1750	1550

*Stage IIIA Engine.

Please see product spec sheets for further information.







20 – 45 kVA DIESEL GENERATOR RANGE

Model	Type – Open, Canopy, Container	Engine	PRIME POWER (PRP)		STANDBY POWER (ESP)		DIMENSIONS (mm)			Weight Including Oil and Water
			50Hz 400V (kVA)	50Hz 400V (kVA)	60Hz 480V (kW)	60Hz 480V (kW)	Length (mm)	Width (mm)	Height (mm)	
G20QS*		JCB Diesel by Kohler	18	20	16	18	1750	790	1350	800
G20S		JCB Diesel by Kohler	18	20	16	18	1650	650	1200	590
G27QS*		JCB Diesel by Kohler	25	27	20	22	2250	840	1350	1000
G27S		JCB Diesel by Kohler	25	27	20	22	1650	650	1250	730
G33QS		JCB Diesel by Kohler	31	34	-	-	2250	840	1350	1000
G33S		JCB Diesel by Kohler	31	34	-	-	2075	670	1250	780
G40QS		JCB Diesel by Kohler	-	-	27	30	2250	840	1350	1000
G40S		JCB Diesel by Kohler	36	39	27	30	2075	670	1250	780
G41QS*		JCB Diesel by Kohler	36	39	-	-	2250	840	1350	1000
G45QS		JCB Diesel by Kohler	41	45	-	-	2250	840	1350	1000
G45S		JCB Diesel by Kohler	41	45	-	-	2075	670	1270	780

*Stage IIIA Engine.

Please see product spec sheets for further information.

165 – 220 kVA DIESEL GENERATOR RANGE

Model	Type – Open, Canopy, Container	Engine	PRIME POWER (PRP)		STANDBY POWER (ESP)		DIMENSIONS (mm)			
			50Hz 400V (kVA)	50Hz 400V (kVA)	60Hz 480V (kW)	60Hz 480V (kW)	Length (mm)	Width (mm)	Height (mm)	Weight Including Oil and Water
G165QS		JCB 6-Cylinder	150	165	125	139	3800	1140	2000	2700
G165S		JCB 6-Cylinder	150	165	125	139	2840	1030	1800	2060
G200QS		JCB 6-Cylinder	180	198	149	165	3800	1140	2000	2700
G200S		JCB 6-Cylinder	180	198	149	165	2840	1030	1800	2090
G220QS		JCB 6-Cylinder	199	219	163	183	3800	1140	2000	2700
G220S		JCB 6-Cylinder	199	219	163	183	2840	1030	1800	2125

*Stage IIIA Engine.

Please see product spec sheets for further information